



RDS-31 S/R

Multi-purpose Survey Meter

The new RDS-31S/R Multi-purpose Survey Meter continues the line of RADOS survey meters offering modern design and approach to radiation monitoring.

RDS-31 is a small handheld, battery operated survey instrument using an energy compensated GM-tube as primary detector. Due to its versatile functions and durability it is suited for a wide range of applications in civil defense, industrial and laboratory use etc.

RDS-31 features excellent ergonomics; light weight and easy handling, with visual and audible alarms and internal vibrator. The large graphic display with Energy Save Backlight is well visible even in sunny conditions due to the illumination control.

To extend the capabilities of the instrument, external probes GMP-25/11-3/15-3/12-series and ABP-150 can be connected to RDS-31S/R directly through binder connector.

User protection while using external probe by measuring simultaneously instrument dose rate.

FEATURES

- H*(10) ambient dose equivalent dose and dose rate
- wide range of external alpha, beta and gamma probes for direct connection with RDS-31
- new ergonomic design
- large graphic screen, configurable backlight with automatic illumination control
- high impact durable case construction, IP-67 immersion proof
- internal memory to store measurements
- flexible histogram functions
- firmware of instrument upgradable through cable link
- configurable shortcut functions

health physics

A Mirion Technologies Division

Featuring:

RADOS



TECHNICAL SPECIFICATIONS:

Radiological Characteristics	<ul style="list-style-type: none"> radiation detected: gamma and X-rays, 48keV...3MeV. Alpha, Beta radiation with an external probe detectors: one energy-compensated GM tube, energy response according to ambient dose equivalent H*(10) dose rate measurement range: 0.01 µSv/h...0.1 Sv/h or 1 µrem/h...10 rem/h dose measurement range: 0.01 µSv...10 Sv or 1 µrem...1000 rem resolution: three significant digits or 0.01 µSv/h on dose rate and 0.01 µSv on dose (1 µrem/h on dose rate and 1 µrem on dose) calibration accuracy: ± 5%, ¹³⁷Cs , calibration direction and in the calibration field, temperature +20 °C (68°F) dose rate linearity: ± 15% ± least significant number 0.05 µSv/h...0.1 Sv/h (5 µrem/h to 10rem/h) variation of the response due to photon radiation energy and angle of incidence: (R_{E,A}) 71% < R_{E,A} < 160% (48 keV...3 MeV); ± 60°
Functional Characteristics	<ul style="list-style-type: none"> two buttons to operate the instrument configurable units: Sv(/h), R(/h), with external detector Gy(/h), cps, cpm, dpm and Bq flexible histogram functions (dose rate, dose, diagnostic logging depending on configuration, time stamp, optional location control for mapping and repeating room measurement analysis) additional histogram analyzing capabilities on CSW-software real time clock function configurable audible, visual and vibration alarm RF-communication and USB-communication with suitable adapter 128x64 pixel graphic display with special symbols for alarm, external probe, battery, RF-communication, vibration alarm, chirp and mute
Electrical Characteristics	<ul style="list-style-type: none"> power supply: 2 AA size batteries (alkaline or NiMH) contacts for external power and charging of NiMH battery (charging conditions +5... +35°C) operation time with fresh alkaline batteries more than 4 months at background radiation at +23°C, 8 h use/24h operation time with fully charged NiMH batteries more than 1 month at background radiation at +23°C, 8 h use/24h. At higher/lower temperatures the operation will be shorter.
Mechanical Characteristics	<ul style="list-style-type: none"> case high impact durable plastics reinforced with glass fibre ergonomic design, rubber grip and cushion around the case enclosure class IP67 (IEC 60529), water proof including battery compartment dimensions: 100 x 67 x 33 mm (3.93 x 2.63 x 1.29 in) weight: 175 g without batteries (0.385 lb), 220 g with batteries (0.485 lb) wrist/neck strap belt clip
Environmental Characteristics	<ul style="list-style-type: none"> -25°C...+60°C (-40°F to 131°F), operating temperature -40°C...+70°C (-40°F to 158°F), storage temperature relative humidity: up to 85% at +35°C (95 °F) fulfills the RF-immunity levels of applicable standard
Options	<ul style="list-style-type: none"> electrical cradle or mechanical cradle e.g. for easy vehicle fixing table top model pocket/belt clip/pouch

Connection of GMP-12 series, GMP-11/15, TGS and Alpha external probes through a suitable cable/adaptor.

NOTE: SINCE NORMS, SPECIFICATIONS AND DESIGNS ARE SUBJECT TO OCCASIONAL CHANGE, PLEASE ASK FOR CONFIRMATION OF THE INFORMATION GIVEN IN THIS PUBLICATION



www.mirion.com
www.hp-mirion.com
20996078_RDS31_EN_C

Mirion Technologies (MGPI) Inc
5000 Highlands Parkway
Suite 150
Smyrna Georgia 30082
USA
T +1.770.432.2744
F +1.770.432.9179

Mirion Technologies (MGPI) SA
Lieu-Dit Calès,
Route d'Eyguières
F-13113 Lamanon
France
T +33 (0) 4 90 59 59 59
F +33 (0) 4 90 59 55 18

Mirion Technologies (RADOS) Oy
P.O. Box 506
FIN-20101 Turku
Finland
T +358 2 468 4600
F +358 2 468 4601

Mirion Technologies (RADOS) GmbH
Ruhrstrasse 49
DE-22761 Hamburg
Germany
T +49 (0) 40 851 93-0
F +49 (0)40 851 93 256

Mirion Technologies Shanghai Branch
Room 801, 78 Jiangchang
San Lu, Zhabei District
Shanghai 200436
China
T +86 21 6180 6920
F +86 21 6180 6924